

Tact switches 6×3.5

INT-1101V Series 6×3.5mm, Through hole type, Side push



- **Features** : Suitable for high-density mounting
- **Applications** : Operating switches for all kinds of electronic equipments
- **Specifications** :

Rating	DC 12V 50mA
Contact resistance	500mΩ Max.
Travel (mm)	0.25±0.1

► Part list

Part No.	Length (mm)		Operating force	Life	QTY per pack (Plastic bag)
	L1	L2			
INT-1101V43AL	3.15	0.7	180±50gf	100,000 Cycles Min.	2K
INT-1101V50AL	3.85	1.4			
INT-1101V65AL	5.35	2.9			
INT-1101V43BL	3.15	0.7	250±50gf		
INT-1101V50BL	3.85	1.4			
INT-1101V65BL	5.35	2.9			

► Drawing

0.5 MAX
3.00
L ±0.2

7.30±0.1
0.50
7.00±0.2
8.5±0.3
2.50
2.5±0.1
4.30±0.2

L2 ±0.1
6.0±0.2
6.60±0.2
1.5
1.0
1.0
2.50
L1 ±0.2

Circuit diagram

2-Ø1.3 HOLES
1.25
1.25
5.0
7.0
2-Ø1 HOLES

PCB Dimension