

# Tact switches 6×6

**INT-1102B Series** 6×6mm, Through hole type



- **Features** : Broad of stem length & Suitable for variety of controls
- **Applications** : Operating switches for all kinds of electronic equipments
- **Specifications** :

Rating	DC 12V 50mA
Contact resistance	100mΩ Max.
Travel (mm)	0.25+0.2/-0.1

## ► Part list

Part No.	Length (mm)	Operating force		Life	QTY per pack (Plastic bag)
		A	B		
INT-1102B43A	INT-1102B43B	4.3			
INT-1102B50A	INT-1102B50B	5.0			
INT-1102B60A	INT-1102B60B	6.0			
INT-1102B70A	INT-1102B70B	7.0			
INT-1102B73A	INT-1102B73B	7.3			
INT-1102B75A	INT-1102B75B	7.5			
INT-1102B80A	INT-1102B80B	8.0			
INT-1102B85A	INT-1102B85B	8.5			
INT-1102B95A	INT-1102B95B	9.5	160±50gf	250±50gf	100,000 Cycles Min.
INT-1102B11A	INT-1102B11B	11.0			2K
INT-1102B12A	INT-1102B12B	12.0			
INT-1102B125A	INT-1102B125B	12.5			
INT-1102B13A	INT-1102B13B	13.0			
INT-1102B135A	INT-1102B135B	13.5			
INT-1102B145A	INT-1102B145B	14.5			
INT-1102B162A	INT-1102B162B	16.2			
INT-1102B17A	INT-1102B17B	17.0			

## ► Drawing

Top view dimensions: 6.0±0.1, 4±0.7, 4.5, 6.0±0.1, 6.5±0.2, 7.9±0.3, 10.3, 3.5±0.2, 1.8, 3.6, L±0.2, 0.5 MAX, 4.5, 4±0.7.

Side view dimensions: 4.5, 4±0.7.

Detail view dimensions: 4±0.7, 4.5.

**Circuit diagram**

**PCB Dimension**

4-Ø1.00±0.05 HOLES, 4.5±0.1, 6.5±0.1

TACT Switches

PUSH Switches

HOOK Switches

DETECTOR Switches

SLIDE Switches

ROTARY Potentiometers

LEVER Switches

ROTARY Switches

CAPS