

Mouse switches

INT-1135B Series 6.2×6.2mm, Through hole type



- ▶ **Features** : Long operating life & Soft operating feeling
- ▶ **Applications** : Telecommunications, Computer, Peripherals, Consumer electronics
- ▶ **Specifications** :

| | |
|--------------------|-------------|
| Rating | DC 12V 50mA |
| Contact resistance | 100mΩ Max. |
| Travel (mm) | 0.3±0.2 |

▶ **Part list**

| Part No. | Length (mm) | Operating force | Life | QTY per pack (Plastic bag) |
|--------------|-------------|-----------------|-----------------------|----------------------------|
| INT-1135B73A | 7.3 | 60±50gf | 1,000,000 Cycles Min. | 2K |
| INT-1135B73B | | 120±50gf | | |

▶ **Drawing**

The drawing includes the following components:

- Top View:** Shows a square footprint with dimensions 6.20±0.1 mm and 5.70 mm. It features four mounting holes with a diameter of Ø3.0 mm.
- Side View:** Shows the profile of the switch with dimensions: 1.0 mm (top), 0.5 MAX (height), 1.9 mm (height), 4.7 mm (height), 7.3±0.2 mm (total length), 3.4±0.2 mm (height), 2-0.8 mm (width), and 5.0 mm (width).
- Cross-sectional View:** Shows the internal mechanism with dimensions: 2.60 mm (width), 1.8 mm (height), 1±0.3 mm (height), and 0.9±0.1 mm (height).
- Circuit Diagram:** A simple switch symbol with terminals labeled ① and ②.
- PCB Dimension:** Shows two circular holes with a diameter of Ø1.0 mm, spaced 5.0 mm apart.

- TACT Switches
- PUSH Switches
- HOOK Switches
- DETECTOR Switches
- SLIDE Switches
- ROTARY Potentiometers
- LEVER Switches
- ROTARY Switches
- CAPS