

Waterproof switches

INT-1136J Series 6.2×6.2mm, Ø2.9mm Stem, Metal cover, Surface mount type, Terminal spacing of 4.0mm



- ▶ **Features :** IP67 dust & water resistance
- ▶ **Applications :** Home appliances or Industrial equipments used around water
- ▶ **Specifications :**

Rating	DC 12V 50mA
Contact resistance	100mΩ Max.
Travel (mm)	0.3±0.1

▶ Part list

Part No.	Length (mm)	Operating force	Life	QTY per pack (Tape & reel)
INT-1136J31A	3.1	200±50gf	350,000 Cycles Min.	1.6K
INT-1136J35A	3.5			
INT-1136J43A	4.3			
INT-1136J50A	5.0			
INT-1136J95A	9.5			
INT-1136J31B	3.1	300±70gf		1.6K
INT-1136J35B	3.5			
INT-1136J43B	4.3			
INT-1136J50B	5.0			
INT-1136J95B	9.5			

▶ Drawing

Terminal spacing of 4.0mm

Top view dimensions: 6.2±0.1 (width), 6.2±0.1 (height), 4±0.7 (terminal offset), 4.0 (terminal spacing).

Side view dimensions: 0.5 MAX (height), 2.3 (height), 2.55 (height), L±0.2 (height), 4.0 (width), 6.6±0.3 (width), 1:0.30 (slope).

Front view dimensions: 4.0 (width), 4.0 (width).

Circuit diagram

PCB Dimension

PCB dimension: 8.6 (width), 3 max (width), 4 (height).

TACT Switches
 PUSH Switches
 HOOK Switches
 DETECTOR Switches
 SLIDE Switches
 ROTARY Potentiometers
 LEVER Switches
 ROTARY Switches
 CAPS