

# Waterproof switches

**INT-1136U Series** 6.2×6.2mm, Ø2.9mm Stem, Metal cover, Surface mount type, Terminal spacing of 4.0mm



- **Features** : IP67 dust & water resistance
- **Applications** : Home appliances or Industrial equipments used around water
- **Specifications** :

Rating	DC 12V 50mA
Contact resistance	100mΩ Max.
Travel (mm)	0.3±0.1

## ► Part list

Part No.	Length (mm)	Operating force	Life	QTY per pack (Tape & reel)
INT-1136U31A	3.1	200±50gf	350,000 Cycles Min.	1.6K
INT-1136U35A	3.5			
INT-1136U43A	4.3			
INT-1136U50A	5.0			
INT-1136U95A	9.5			
INT-1136U31B	3.1	300±70gf		1.6K
INT-1136U35B	3.5			
INT-1136U43B	4.3			
INT-1136U50B	5.0			
INT-1136U95B	9.5			

## ► Drawing

Terminal spacing of 4.0mm

**Circuit diagram**

**PCB Dimension**

TACT Switches  
 PUSH Switches  
 HOOK Switches  
 DETECTOR Switches  
 SLIDE Switches  
 ROTARY Potentiometers  
 LEVER Switches  
 ROTARY Switches  
 CAPS