

SMT Tact switches

INT-1157AG Series

6.2×6.5mm with 2.6mm high case, Surface mount type with Ground pin



- **Features** : Suitable for variety of controls
- **Applications** : Audio, TV, Communication devices, Operating switches for all kinds of electronic equipments
- **Specifications** :

Rating	DC 12V 50mA
Contact resistance	100mΩ Max.
Travel (mm)	0.25±0.1

► Part list

Part No.	Length (mm)	Operating force	Pitch (mm)	Life	QTY per pack (Tape & reel)		
INT-1157AG29AO	2.9	160±50gf	8.00	100,000 Cycles Min.	1.5K (1.7K)		
INT-1157AG31AO	3.1						
INT-1157AG34AO	3.4						
INT-1157AG43AO	4.3						
INT-1157AG29BO	2.9	250±50gf	8.00		100,000 Cycles Min.	1K	
INT-1157AG31BO	3.1						
INT-1157AG34BO	3.4						
INT-1157AG43BO	4.3						
INT-1157AG29AQ	2.9	160±50gf	10.00			100,000 Cycles Min.	1.5K (1.7K)
INT-1157AG31AQ	3.1						
INT-1157AG34AQ	3.4						
INT-1157AG43AQ	4.3						
INT-1157AG29BQ	2.9	250±50gf	10.00	100,000 Cycles Min.			1K
INT-1157AG31BQ	3.1						
INT-1157AG34BQ	3.4						
INT-1157AG43BQ	4.3						

* Long life (1KK cycles) is available and part numbers in long life change to INT-1157AG29AOL / INT-1157AG29AQL~ INT-1157AG43AOL / INT-1157AG43AQL.

► Drawing

