

# Sealed SMT Tact switches

## INT-1162J Series

6.2×6.2mm, Sealed with Rubber stem, Surface mount type



- **Features :** Rubber stem provides soft feeling
- **Applications :** PC & Peripherals, Car AV equipments, Automobile, Communications devices
- **Specifications :**

Rating	DC 12V 50mA
Contact resistance	100mΩ Max.
Travel (mm)	0.4+0.2/-0.1

### ► Part list

Part No.	Length (mm)	Operating force	Life	QTY per pack (Tape & reel)
INT-1162J26A	2.6	200±100gf	100,000 Cycles Min.	1.6K
INT-1162J34A	3.4			
INT-1162J38A	3.8			
INT-1162J43A	4.3			
INT-1162J45A	4.5			
INT-1162J49A	4.9			
INT-1162J51A	5.1			
INT-1162J55A	5.5			
INT-1162J26B	2.6	300±100gf		1.6K
INT-1162J34B	3.4			
INT-1162J38B	3.8			
INT-1162J43B	4.3			
INT-1162J45B	4.5			
INT-1162J49B	4.9			
INT-1162J51B	5.1			
INT-1162J55B	5.5	1K		

\* Long life (1KK cycles) is available and part numbers in long life change to INT-1162J26AL~INT-1162J55AL

### ► Drawing

