

Subminiature Tact switches

INT-1410F Series 3.9×3mm with 2.0 & 2.5mm length, Dustproof, Surface mount type



► **Features** : Subminiature design, Sealed contact ensures dust resistance.

► **Applications** : Smartphones, Other mobile devices, Consumer electronics

► **Specifications** :

Rating	DC 12V 50mA
Contact resistance	100mΩ Max.
Travel (mm)	0.15±0.1

► **Part list**

Part No.	Length (mm)	Operating force	Life	QTY per pack (Tape & reel)	Remarks
INT-1410F20A	2.0	160±50gf	50,000 Cycles Min.	3K	without guide bosses
INT-1410F25A	2.5	250±50gf			
INT-1410F20B	2.0	160±50gf			
INT-1410F25B	2.5	250±50gf			
INT-1410FE20A	2.0	160±50gf			with guide bosses
INT-1410FE25A	2.5	250±50gf			
INT-1410FE20B	2.0	160±50gf			
INT-1410FE25B	2.5	250±50gf			

► **Drawing**

Without guide bosses		With guide bosses	
	<p>Circuit diagram</p>		<p>Circuit diagram</p>
	<p>PCB Dimension</p>		<p>PCB Dimension</p>

TACT Switches
 PUSH Switches
 HOOK Switches
 DETECTOR Switches
 SLIDE Switches
 ROTARY Potentiometers
 LEVER Switches
 ROTARY Switches
 CAPS