

Subminiature Tact switches

INT-1440F Series 3.9×3.0mm with 2.0 & 2.5mm length, Surface mount type

- TACT Switches
- PUSH Switches
- HOOK Switches
- DETECTOR Switches
- SLIDE Switches
- ROTARY Potentiometers
- LEVER Switches
- ROTARY Switches
- CAPS



- ▶ **Features** : Subminiature design
- ▶ **Applications** : Smartphones, Other mobile devices, Consumer electronics
- ▶ **Specifications** :

Rating	DC 12V 50mA
Contact resistance	100mΩ Max.
Travel (mm)	0.15±0.1

▶ Part list

Part No.	Length (mm)	Operating force	Life	QTY per pack (Tape & reel)	Remarks
INT-1440F20A	2.0	160±50gf	50,000 Cycles Min.	3K	without guide bosses
INT-1440F25A	2.5	160±50gf			
INT-1440F20B	2.0	250±50gf			
INT-1440F25B	2.5	250±50gf			
INT-1440FE20A	2.0	160±50gf			with guide bosses
INT-1440FE25A	2.5	160±50gf			
INT-1440FE20B	2.0	250±50gf			
INT-1440FE25B	2.5	250±50gf			

▶ Drawing

Without guide bosses		With guide bosses	
	<p style="text-align: center;">Circuit diagram</p>	<p style="text-align: center;">PCB Dimension</p>	
	<p style="text-align: center;">Circuit diagram</p>	<p style="text-align: center;">PCB Dimension</p>	